## COPPERHEAD INTEL Powered By DCC



#### Automatic screen printing press New Facelift Version 2



M&R Global's Copperhead Intel automatic oval screen printing press combines high volume throughput, and durable construction with the latest features in oval press design. The Intel comes standard with electronic printheads, pneumatic frame locks, independent controls for print & flood speeds, and the full suite of automatic programming that work in either clockwise or counter-clockwise printing configurations.

Intel comes in a standard Print/Flash/Print (PFP) configuration that is one of the most popular choices preferred by printers around the world. The Copperhead Intel is modifiable up to 64 station configurations to accommodate different printing and flashing needs and the indexing system includes an auto-tensioning feature on the chain to minimize wear.

Each Intel printhead utilizes the patented squeegee pressure equalizer system which maintains a uniform squeegee pressure across the entire print area to minimize printing pressure, maintain image detail, and avoid ink deposit variation. All standard Intel pallets are solid, lightweight aluminum with rubber coating to better manage heat during flashing.

The Copperhead Intel oval is assembled with the highest quality, globally sourced components and manufactured for consistency and durability. With all of the features of Copperhead series presses, and the flexible yet powerful oval press format, the Intel oval has the right combination for your high-volume printing needs.

### **FEATURES**

- Standard Image Size: 51 x 71 cm (20" x 28")
- Double Index Image Size: 91 x 70 cm (36" x 28")
- Standard Pallet Size: 60 x 89 cm (23.5" x 35")
- Servo Indexing System
- Centralized pallet locking system for precise registration
- Auto tensioning chain mechanism to increase life of machine
- High-Resolution Touchscreen Control Panel with Easy-to-use, Icon-based Logic and Built-in Tutorial Screens

Find more information and where to buy at: www.mrprintglobal.com



# COPPERHEAD INTEL Powered By DCC

## **Smooth Servo Indexer • Modular Design • Production Efficiency!**

Copperhead Intel features a squeegee equalizer system with individual regulators on each head ensures uniform ink deposit for excellent print quality.

With up to 64 stations configurations, there is sure to be Copperhead Intel that meets your needs.



The Squeegee Equalizer System



**Smart Lube Technology automatically** lubricates press components, ensuring longevity and optimal performance.

SPECIFICATIONS	INTEL 5171 20/8	INTEL 5171 28/12	INTEL 5171 32/14	INTEL 5171 40/18	INTEL 5171 44/20	INTEL 5171 52/24	INTEL 5171 56/26	INTEL 5171 64/30
Air @ 7 Bar (102 psi)	1430 l/min (51 cfm)	2090 I/min (74 cfm)	2420 I/min (86 cfm)	3080 I/min (109 cfm)	3410 l/min (120 cfm)	4070 I/min (144 cfm)	4400 I/min (155 cfm)	5060 I/min (179 cfm)
Electrical Requirements <sup>1</sup>	208-230 V, 3 ph, 15 A, 50/60 Hz, 4.75kW (UL) 380-415 V, 3 ph, 11.5 A, 50 Hz, 4.75kW (CE)	208-230 V, 3 ph, 20 A, 50/60 Hz, 6.25kW (UL) 380-415 V, 3 ph, 16.5 A 50 Hz, 6.25kW (CE)	208-230 V, 3 ph, 22 A, 50/60 Hz, 7kW (UL) 380-415 V, 3 ph, 16.5 A, 50 Hz, 7kW (CE)	208-230 V, 3 ph, 27 A, 50/60 Hz, 8.5kW (UL) 380-415 V, 3 ph, 21 A, 50 Hz, 8.5kW (CE)	208-230 V, 3 ph, 29.5 A, 50/60 Hz, 9.25kW (UL) 380-415 V, 3 ph, 21 A, 50 Hz, 9.25kW (CE)	208-230 V, 3 ph, 34 A, 50/60 Hz, 10.75kW (UL) 380-415 V, 3 ph, 24.5 A, 50 Hz, 10.75kW (CE)	208-230 V, 3 ph, 36.5 A, 50/60 Hz, 11.5kW (UL) 380-415 V, 3 ph, 24.5 A, 50 Hz, 11.5kW (CE)	208-230 V, 3 ph, 41 A, 50/60 Hz, 13kW (UL) 380-415 V, 3 ph, 29 A, 50 Hz, 13kW (CE)
Standard Image Size	51 x 71 cm (20" x 28")	51 x 71 cm (20" x 28")	51 x 71 cm (20" x 28")	51 x 71 cm (20" x 28")	51 x 71 cm (20" x 28")	51 x 71 cm (20" x 28")	51 x 71 cm (20" x 28")	51 x 71 cm (20" x 28")
Standard Pallet Size	60 x 89 cm (23.5" x 35")	60 x 89 cm (23.5" x 35")	60 x 89 cm (23.5" x 35")	60 x 89 cm (23.5" x 35")	60 x 89 cm (23.5" x 35")	60 x 89 cm (23.5" x 35")	60 x 89 cm (23.5" x 35")	60 x 89 cm (23.5" x 35")
Standard Frame Size (OD)	66 x 109 cm (26" x 43")	66 x 109 cm (26" x 43")	66 x 109 cm (26" x 43")	66 x 109 cm (26" x 43")	66 x 109 cm (26" x 43")	66 x 109 cm (26" x 43")	66 x 109 cm (26" x 43")	66 x 109 cm (26" x 43")
Maximum Image Size (Double Index)	91 x 71 cm (36" x 28")	91 x 71 cm (36" x 28")	91 x 71 cm (36" x 28")	91 x 71 cm (36" x 28")	91 x 71 cm (36" x 28")	91 x 71 cm (36" x 28")	91 x 71 cm (36" x 28")	91 x 71 cm (36" x 28")
Double Index Pallet Size	97 x 89 cm (38" x 35")	97 x 89 cm (38" x 35")	97 x 89 cm (38" x 35")	97 x 89 cm (38" x 35")	97 x 89 cm (38" x 35")	97 x 89 cm (38" x 35")	97 x 89 cm (38" x 35")	97 x 89 cm (38" x 35")
Double Index Frame Size	112 x 109 cm (44" x 43")	112 x 109 cm (44" x 43")	112 x 109 cm (44" x 43")	112 x 109 cm (44" x 43")	112 x 109 cm (44" x 43")	112 x 109 cm (44" x 43")	112 x 109 cm (44" x 43")	112 x 109 cm (44" x 43")
Overall Size (L x W x H)	864 x 358 x 209 cm (340" x 141" x 82")	1162 x 358 x 209 cm (458" x 141" x 82")	1311 x 358 x 209 cm (516" x 141" x 82")	1609 x 358 x 209 cm (634" x 141" x 82")	1758 x 358 x 209 cm (692" x 141" x 82")	2057 x 358 x 209 cm (809" x 141" x 82")	2206 x 358 x 209 cm (869" x 141" x 82")	2504 x 358 x 209 cm (986" x 141" x 82")
Stations/Colors	20/8	28/12	32/14	40/18	44/20	52/24	56/26	64/30
He wisterweith any county (IDC) to a favored making from white fluctuation out of main county of minimum than different the college (A) listed in the breakure admitted								

Use uninterruptible power supply (UPS) to safeguard machine from voltage fluctuation out of main supply. If incoming voltage differs from the voltage(s) listed in the brochure, calculate amperage accordingly.

M&R Printing Equipment, Inc. • www.mrprint.com 440 Medinah Road, Roselle, Illinois 60172-2329 USA

DCC Group • www.mrprintglobal.com 802, Kamla Executive Park, JB Nagar, Andheri (E), Mumbai, 400059, India

USA: 800-736-6431 / 630-858-6101 • Outside USA: +1-847-967-4461 • India: +91 98719-88775

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for damages, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No warranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2022 M&R Printing Equipment, Inc. All rights reserved. 20230807E