


Automatic screen printing press



M&R Global's Copperhead Rival™ presses are a the benchmark in automatic screen printing presses, combining highest quality components, leading-class craftsmanship and high-speed production to create an outstanding press at an affordable price.

An electric indexing system enables extremely smooth and quiet operation. The included, innovative squeegee pressure equalizer system with regulators on each printhead speeds setup and ensures uniform ink deposit for excellent print quality.

Electric printheads, tool-free squeegee/floodbar angle adjustment, pneumatic screen frame clamps and independent squeegee/flood speeds provide operators with all the time-saving features needed for quick setups. The Copperhead Rival is compatible with M&R Tri-Loc® system for the ultimate in print registration speed, accuracy and consistency.


FEATURES

- Available In 1 and 3 phase
- Available In 8, 10, 12 and 14 Stations
- Standard Pallet Size: 40 x 63 cm (16" x 25")
- Standard Image Area: 40 x 50 cm (16" x 20")
- Standard Front- and Rear-Locking Micro-Registration
- Standard Pneumatic Screen Frame Clamps
- High-Resolution Touchscreen Control Panel with Easy-to-Use, Icon-Based Logic and Built-In Tutorial Screens
- Print Stack Mode Enables HD and Other Specialty Print Techniques


Smooth Print Strokes • Quiet Operation • Tool-Free Adjustments

Copperhead Rival features a squeegee equalizer system with individual regulators on each head ensures uniform ink deposit for excellent print quality.

With 8, 10, 12 & 14 station configurations, there is sure to be a Copperhead Rival that meets your needs.



Printhead controls are conveniently located for easy access and adjustment



Individual mechanical heads lift for quick screen cleaning

SPECIFICATIONS	RIVAL 8/6	RIVAL 10/8	RIVAL 12/10	RIVAL 14/12
Air @ 7 Bar (102 psi)	495 l/min (17.5 cfm)	565 l/min (20.0 cfm)	755 l/min (26.7 cfm)	825 l/min (29.1 cfm)
Electrical Requirements ¹	208-230 V, 1 ph, 18A, 50/60 Hz, 3.25 kW (UL/CE) 208-230 V, 3 ph, 10.5A, 50/60 Hz, 3.25 kW (UL) 380-415 V, 3 ph, 7A, 50 Hz, 3.25 kW (CE)	208-230 V, 1 ph, 22A, 50/60 Hz, 4 kW (UL/CE) 208-230 V, 3 ph, 15A, 50/60 Hz, 4 kW (UL) 380-415 V, 3 ph, 10A, 50 Hz, 4 kW (CE)	208-230 V, 1 ph, 26A, 50/60 Hz, 4.75 kW (UL/CE) 208-230 V, 3 ph, 15A, 50/60 Hz, 4.75 kW (UL) 380-415 V, 3 ph, 10A, 50 Hz, 4.75 kW (CE)	208-230 V, 1 ph, 30A, 50/60 Hz, 5.5 kW (UL/CE) 208-230 V, 3 ph, 17.5A, 50/60 Hz, 5.5 kW (UL) 380-415 V, 3 ph, 14A, 50 Hz, 5.5 kW (CE)
Diameter	391 cm (154")	416 cm (164")	448 cm (176")	472 cm (185")
Maximum Frame Size	58 x 84 cm (23" x 33")	58 x 84 cm (23" x 33")	58 x 84 cm (23" x 33")	58 x 84 cm (23" x 33")
Standard Image Area	41 x 51 cm (16" x 20")	41 x 51 cm (16" x 20")	41 x 51 cm (16" x 20")	41 x 51 cm (16" x 20")
Maximum Rated Image Area	46 x 51 cm (18" x 20")	46 x 51 cm (18" x 20")	46 x 51 cm (18" x 20")	46 x 51 cm (18" x 20")
Machine Weight	1257 kg (2771 lb)	1592 kg (3510 lb)	1822 kg (4017 lb)	2350 kg (5181 lb)
Standard Pallet Size	41 x 64 cm (16" x 25")	41 x 64 cm (16" x 25")	41 x 64 cm (16" x 25")	41 x 64 cm (16" x 25")
Stations/Colors	8/6	10/8	12/10	14/12

¹ Use uninterruptible power supply (UPS) to safeguard machine from voltage fluctuation out of main supply. If incoming voltage differs from the voltage(s) listed in the brochure, calculate amperage accordingly. Contact M&R Global/ your nearest dealer for total amperage in case of using built-in flash sockets.

M&R Printing Equipment, Inc. • www.mrprint.com
440 Medinah Road, Roselle, Illinois 60172-2329 USA

DCC Group • www.mrprintglobal.com
802, Kamla Executive Park, JB Nagar, Andheri (E), Mumbai, 400059, India

USA: 800-736-6431 / 630-858-6101 • Outside USA: +1-847-967-4461 • India: +91 98719-88775

M&R Printing Equipment, Inc. and its subsidiaries (hereinafter M&R), believe the information in this advertisement to be accurate at publication, though it does not purport to list all manufacturing and specification variations, nor does it assume liability resulting from incompleteness or inaccuracy. M&R reserves the right to change specifications without notice. M&R expressly disclaims any liability for damages, consequential or incidental, from purchase, installation, servicing, and/or use of any product/service based upon information herein. No warranties of merchantability or fitness for a particular purpose are made or are to be implied from the information herein. No information herein may be reproduced or used in any manner without the prior, express written consent of M&R in each case. Copyright 2022 M&R Printing Equipment, Inc. All rights reserved. 20240809P